06-02342

SAFETY DATA SHEET

MOLYKOTE(R) 33 EXTREME LOW TEMP. **BEARING GREASE, LIGHT**



Version 3.0

Revision Date:

09/14/2017

SDS Number: 935842-00010 Date of last issue: 03/10/2017

Date of first issue: 12/11/2014

SECTION 1. IDENTIFICATION

Product name

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING

GREASE, LIGHT

Product code

00000000001889770

Manufacturer or supplier's details

Company name of supplier

Dow Corning Corporation

Address

South Saginaw Road

Midland Michigan 48686

Telephone

(989) 496-6000

Emergency telephone

24 Hour Emergency Telephone: (989) 496-5900

CHEMTREC: (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use

: Lubricants and lubricant additives

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910,1200

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

Mixture

Chemical nature

Silicone grease

Hazardous ingredients

Chemical name	* .	CAS-No.	Concentration (% w/w)
Lithium stearate		4485-12-5	>= 12 - <= 18

SECTION 4. FIRST AID MEASURES

If inhaled

If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

n case of skin contact

Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT



Version

Revision Date:

SDS Number:

Date of last issue: 03/10/2017

3.0

09/14/2017

935842-00010

Date of first issue: 12/11/2014

In case of eye contact

Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed

If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed

None known.

Protection of first-aiders

No special precautions are necessary for first aid responders.

Notes to physician

Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- :

ucts

Carbon oxides Silicon oxides

Formaldehyde Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions

Discharge into the environment must be avoided.

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT



Version 3.0

Revision Date: 09/14/2017

SDS Number: 935842-00010

Date of last issue: 03/10/2017 Date of first issue: 12/11/2014

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures

: See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation

Use only with adequate ventilation.

Advice on safe handling

Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure

assessment

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage

Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid

Do not store with the following product types:

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

		_		
Ingredients	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
	A. (.)	exposure)	concentration	
Lithium stearate	4485-12-5	TWA	10 mg/m³	l acgih - I

Engineering measures

Processing may form hazardous compounds (see section

10).

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT



Version 3.0

Revision Date:

09/14/2017

SDS Number: 935842-00010

Date of last issue: 03/10/2017 Date of first issue: 12/11/2014

Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Remarks

Wash hands before breaks and at the end of workday.

Eye protection

Wear the following personal protective equipment:

Safety glasses

Skin and body protection

Skin should be washed after contact.

Hygiene measures

Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may

require added precautions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Grease

Color

white

Odor

slight

Odor Threshold

0001 11110011010

: No data available

рΗ

Not applicable

Melting point/freezing point

No data available

Initial boiling point and boiling

Not applicable

range

Flash point

: > 101.1 °C

Method: closed cup

Evaporation rate

Not applicable

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT



Version 3.0

Revision Date: 09/14/2017

SDS Number: 935842-00010

Date of last issue: 03/10/2017 Date of first issue: 12/11/2014

Flammability (solid, gas)

Not classified as a flammability hazard

Self-ignition

The substance or mixture is not classified as pyrophoric. The

substance or mixture is not classified as self heating.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure

Not applicable

Relative vapor density

No data available

Relative density

1.1

Solubility(ies)

Water solubility

No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature

No data available

Decomposition temperature

No data available

Viscosity

Viscosity, dynamic

Not applicable

Explosive properties

Not explosive

Oxidizing properties

The substance or mixture is not classified as oxidizing.

Molecular weight

: No data available

Particle size

No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not classified as a reactivity hazard.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reac-

tions

Use at elevated temperatures may form highly hazardous

compounds.

Can react with strong oxidizing agents.

Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid

None known.

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT



Version 3.0

Revision Date:

09/14/2017

SDS Number: 935842-00010

Date of last issue: 03/10/2017 Date of first issue: 12/11/2014

Incompatible materials

: Oxidizing agents

Hazardous decomposition products

Thermal decomposition

Benzene

Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Ingredients:

Lithium stearate:

Acute oral toxicity

: LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity

: LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Ingredients:

Lithium stearate:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:

Lithium stearate:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Remarks: Based on data from similar materials

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT



Version 3.0

Revision Date: 09/14/2017

SDS Number: 935842-00010

Date of last issue: 03/10/2017 Date of first issue: 12/11/2014

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:

Lithium stearate:

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse

Method: OECD Test Guideline 429

Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Lithium stearate:

Genotoxicity in vitro

Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Ingredients:

Lithium stearate:

Species: Mouse

Application Route: Skin contact Exposure time: 104 weeks

Result: negative

Remarks: Based on data from similar materials

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

MOLYKOTE(R) 33 EXTREME LOW TEMP. **BEARING GREASE, LIGHT**



Version 3.0

Revision Date:

09/14/2017

SDS Number: 935842-00010 Date of last issue: 03/10/2017 Date of first issue: 12/11/2014

Ingredients:

Lithium stearate:

Effects on fertility

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Skin contact

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development :

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Skin contact

Result: negative

Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Ingredients:

Lithium stearate:

Species: Rat

NOAEL: 88 mg/kg Application Route: Ingestion

Exposure time: 90 Days

Remarks: Based on data from similar materials

Species: Rat

NOAEL: 1,089.75 mg/kg

Application Route: Skin contact

Exposure time: > 43 Days

Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Toxicity to fish

Lithium stearate:

LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

8 / 13

MOLYKOTE(R) 33 EXTREME LOW TEMP. **BEARING GREASE, LIGHT**



Version

Revision Date:

SDS Number: 935842-00010 Date of last issue: 03/10/2017

3.0

09/14/2017

Date of first issue: 12/11/2014

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae

EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to microorganisms

NOEC: 13 mg/l Exposure time: 28 d

Remarks: Based on data from similar materials

Persistence and degradability

Ingredients:

Lithium stearate:

Biodegradability

Result: Readily biodegradable.

Biodegradation: 78 % Exposure time: 28 d

Method: OECD Test Guideline 301C

Remarks: Based on data from similar materials

Bioaccumulative potential

Ingredients:

Lithium stearate:

Bioaccumulation

Species: Fish

Bioconcentration factor (BCF): 0.12

Remarks: Based on data from similar materials

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and Recovery Act (RCRA)

This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded

in its purchased form.

MOLYKOTE(R) 33 EXTREME LOW TEMP. **BEARING GREASE, LIGHT**



Version 3.0

Revision Date:

09/14/2017

SDS Number: 935842-00010 Date of last issue: 03/10/2017 Date of first issue: 12/11/2014

Waste from residues

Dispose of in accordance with local regulations.

Contaminated packaging

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards

: No SARA Hazards

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations


Pennsylvania Right To Know

Dimethyl, phenylmethyl siloxane, trimethyl-terminated

63148-52-7 4485-12-5

Lithium stearate

MOLYKOTE(R) 33 EXTREME LOW TEMP. **BEARING GREASE, LIGHT**



Version 3.0

Revision Date: 09/14/2017

SDS Number: 935842-00010 Date of last issue: 03/10/2017

Date of first issue: 12/11/2014

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California Permissible Exposure Limits for Chemical Contaminants

Lithium stearate

4485-12-5

The ingredients of this product are reported in the following inventories:

NZIoC

: All ingredients listed or exempt.

REACH

For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC

representative/local office.

TSCA

All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

AICS

All ingredients listed or exempt.

IECSC

All ingredients listed or exempt.

ENCS/ISHL

All components are listed on ENCS/ISHL or exempted from

inventory listing.

KECI

All ingredients listed, exempt or notified.

PICCS

All ingredients listed or exempt.

DSL

All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

TCSI

: All ingredients listed or exempt.

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT



Version 3.0

Revision Date: 09/14/2017


SDS Number: 935842-00010

Date of last issue: 03/10/2017 Date of first issue: 12/11/2014

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS® IV:

HEALTH		1	0
FLAMMABILITY			1
PHYSICAL WAZARD	A STATE OF THE PARTY OF THE PAR		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH

USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA

8-hour, time-weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT



Version 3.0

Revision Date: 09/14/2017

SDS Number: 935842-00010

Date of last issue: 03/10/2017 Date of first issue: 12/11/2014

Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date

09/14/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8