

Safety Data Sheet

Page 1 of 8

RETAINING COMPOUND 609 BULK

MSDS-No.: 153471 V001.3 Date of issue: 08.05.2015

Section 1. Identification	of the substance/preparation and of the company/undertaking	
Product name:	RETAINING COMPOUND 609 BULK	
Intended use:	Anaerobic Adhesive	
Supplier: Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia Phone: +61 (3) 9724 6444		
Emergency information:	24 HOUR EMERGENCY CONTACT NUMBER 03 9724 6556	
Section 2. Hazards identification		

Classification of the substance or mixture Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

Hazard Class	Hazard Category
Skin irritation	Category 2
Serious eye irritation	Category 2A
Skin sensitizer	Category 1
Target Organ Systemic Toxicant -	Category 3
Single exposure	
Chronic hazards to the aquatic	Category 3
environment	
Hazard pictogram:	\wedge

Signal word:



Target organ

respiratory tract irritation

Hazard statement(s):	 H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects.
Precautionary Statement(s):	
Prevention:	P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
	P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.
	P272 Contaminated work clothing should not be allowed out of the workplace.
	P273 Avoid release to the environment.
	P280 Wear protective gloves, clothing, eye and face protection.
Response:	P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362 Take off contaminated clothing.
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Classification of material Xi - Irritant

Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin. R43 May cause sensitisation by skin contact. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

S23 Do not breathe vapour.
S24 Avoid contact with skin.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S29 Do not empty into drains.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S46 If swallowed, seek medical advice immediately and show this container or label.
S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Signal word: HAZARDOUS

Section 3. Composition / information on ingredients

General chemical description: General chemical description: Type of preparation: Substance Mixture Anaerobic Sealant

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion	
2-Hydroxyethyl methacryla	te 868-77-9	10- 30 %	
Cumene hydroperoxide	80-15-9	< 3 %	
Methacrylic acid	79-41-4	< 1 %	
non hazardous ingredients	~	60- 100 %	
	Section 4. First aid meas	sures	
Ingestion:	Do not induce vomiting. Have victim rinse mouth thoroughly Seek medical advice.	with water.	
Skin:	Immediately flush skin with plenty of Seek medical advice.	of water (using soap, if available).	
Eyes:	Immediately flush eyes with plenty of Seek medical advice.	of water for at least 15 minutes.	
Inhalation:	Move to fresh air. Keep warm and in a quiet place. Seek medical advice.		
First Aid facilities:	Eye wash Normal washroom facilities		
Medical attention and special treatment:	Treat symptomatically.		

Section 5. Fire fighting measures		
Suitable extinguishing media:	Carbon dioxide, foam, powder	
Decomposition products in case of fire::	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide. Oxides of nitrogen.	
Special protective equipment for fire-fighters:	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). Wear full protective clothing.	
Additional fire fighting advice:	In case of fire, keep containers cool with water spray.	

	Section 6. Accidental release measures
Personal precautions:	Ensure adequate ventilation. Avoid skin and eye contact.
	Wear appropriate personal protective equipment.
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Section 7. Handling and storage		
Precautions for safe handling:	Use only in well-ventilated areas.	
	Avoid skin and eye contact.	
	Wear suitable protective clothing, safety glasses and gloves.	
	Prolonged or repeated skin contact should be avoided	

Conditions for safe storage:

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

Section 8. Exposure controls / personal protection

National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
METHACRYLIC ACID 79-41-4		20	70	-	-	-	-
Engineering controls:	Pro limi	1	ocal exhaust	ventilation to ma	untain worker	exposure below	exposure
Eye protection:	We	ar protective gla	isses.				
Skin protection:		ar suitable prote vid skin-contact		g.			
	Rec	ommended glov	ves include b	utyl rubber and	neoprene.		
	Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.						
Respiratory protection:			· ·	espirator or air s and AS/NZS 171	11	complying with	n the

	Section	9.	Physical	and	chemical	properties
--	---------	----	----------	-----	----------	------------

Appearance:
Odor:
Specific gravity:
Boiling point:
Flash point:
(Tagliabue closed cup)
Vapor pressure:
(; 26 °C (78.8 °F))
Density:
VOC content:
(1999/13/EC)

Green Liquid Mild 1.1 > 150 °C (> 302 °F) > 93.3 °C (> 199.94 °F) < 6 mbar 1.1 g/cm3 < 3.00 %

	Section 10. Stability and reactivity
Stability:	Stable under recommended storage conditions.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.
Incompatible materials:	Reacts with strong oxidants.
Hazardous decomposition products:	Thermal decomposition can lead to release of irritating gases and vapors.
-	Carbon monoxide. Carbon dioxide. Oxides of nitrogen.

Section 11. Toxicological information

Health Effects:	
Ingestion:	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Skin:	Causes skin irritation.
	Symptoms may include redness, edema, drying, defatting and cracking of the skin.
	May cause skin sensitization.
Eyes:	Causes serious eye irritation.
-	Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Inhalation:	This product is irritating to the respiratory system.
	Vapors are irritating to the nose, throat and respiratory tract resulting in dryness of throat and
	tightness in chest. Other symptoms of overexposure include headache, nausea, narcosis, fatigue
	and loss of appetite.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	LD50	> 3,000 mg/kg	dermal		rabbit	
Cumene hydroperoxide 80-15-9	LD50	550 mg/kg	oral		rat	
Methacrylic acid	LD50	1,320 mg/kg	oral		rat	OECD Guideline 401 (Acute
79-41-4	LC50 Acute	4.7 mg/l 500 mg/kg	inhalation dermal	4 h	rat	Oral Toxicity) OECD Guideline 403 (Acute
	toxicity estimate (ATE)	500 - 1,000 mg/kg	dermal		rabbit	Inhalation Toxicity) Expert judgement Dermal Toxicity Screening
	LD50					

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
Methacrylic acid 79-41-4	Category 1A (corrosive)	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	Buehler test

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	negative positive	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test	with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	

Section 12. Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

Ecotoxicity:

Harmful to aquatic life with long lasting effects.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
			Study			
2-Hydroxyethyl methacrylate	LC50	227 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline
868-77-9						203 (Fish, Acute
						Toxicity Test)
2-Hydroxyethyl methacrylate	EC50	380 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
868-77-9						202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
2-Hydroxyethyl methacrylate	EC50	345 mg/l	Algae	72 h	Selenastrum capricornutum	OECD Guideline
868-77-9					(new name: Pseudokirchnerella	201 (Alga, Growth
					subcapitata)	Inhibition Test)
2-Hydroxyethyl methacrylate	NOEC	160 mg/l	Algae	72 h	Selenastrum capricornutum	OECD Guideline
868-77-9					(new name: Pseudokirchnerella	201 (Alga, Growth
]]				subcapitata)	Inhibition Test)
Cumene hydroperoxide	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
80-15-9						203 (Fish, Acute
	ļ					Toxicity Test)
Cumene hydroperoxide	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
80-15-9						202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
Cumene hydroperoxide	ErC50	3.1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline
80-15-9						201 (Alga, Growth
	ļļļ					Inhibition Test)
Methacrylic acid	LC50	85 mg/l	Fish	96 h	Salmo gairdneri (new name:	EPA OTS
79-41-4					Oncorhynchus mykiss)	797.1400 (Fish
						Acute Toxicity
	ļ					Test)
Methacrylic acid	EC50	> 130 mg/l	Daphnia	48 h	Daphnia magna	EPA OTS
79-41-4						797.1300 (Aquatic
						Invertebrate Acute
						Toxicity Test,
						Freshwater
	MORE		1			Daphnids)
Methacrylic acid	NOEC	8.2 mg/l	Algae	72 h	Selenastrum capricornutum	OECD Guideline
79-41-4					(new name: Pseudokirchnerella	201 (Alga, Growth
	5950				subcapitata)	Inhibition Test)
Methacrylic acid	EC50	45 mg/l	Algae	72 h	Selenastrum capricornutum	OECD Guideline
79-41-4					(new name: Pseudokirchnerella	201 (Alga, Growth
ļ			I		subcapitata)	Inhibition Test)

Persistence and degradability:

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		

2-Hydroxyethyl methacrylate 868-77-9	readily biodegradable	aerobic	92 - 100 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Cumene hydroperoxide 80-15-9		9.1		calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene hydroperoxide 80-15-9	2.16					
Methacrylic acid 79-41-4	0.93				22 °C	OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)

	Section 13. Disposal considerations
Waste disposal of product:	Dispose of in accordance with local and national regulations.
Disposal for uncleaned package:	After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated. Disposal must be made according to official regulations.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

General information: Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

Section 15. Regulatory information

SUSMP Poisons Schedule	None
AICS:	All components are listed or are exempt from listing on the Australian Inventory of Chemical Substances (AICS).

	Section 16. Other information
Abbreviations/acronyms:	ADGC - Australian Dangerous Goods Code IMDG: International Maritime Dangerous Goods code IATA-DGR: International Air Transport Association – Dangerous Goods Regulations STEL - Short term exposure limit TWA - Time weighted average
Reason for issue:	Reviewed SDS. Reissued with new date. involved chapters: 1 - 16
Date of previous issue:	05.07.2012
Disclaimer:	The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material. The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited disclaims any liability for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet. This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in t specific context of the material's intended use.