



# CLASSIC COAT™

## TECHNICAL DATA SHEET

---

### *Description*

**CLASSIC COAT** uses advanced technology to provide superior adhesion and flexibility when changing or restoring the color of most leather and vinyl. **CLASSIC COAT** is a fade resistant coating that won't chip or peel and is available in many of today's popular OEM colors.

### *Features*

- Excellent for leather and vinyl
- Convenient aerosol package
- Superior adhesion and flexibility
- OEM matched colors
- Won't chip or peel
- Multidirectional fan spray

### *Typical Properties*

Container	16 oz. aerosol
Colors	35 OEM matched colors
Coats	2-3
VOC	3.76 #/gl (451 g/l)
Cure time	24 hours @ 70°F (21°C)

### *Handling and Application*

#### **PREPARATION:** Vinyl:



1. Clean first with **39362 SEM SOAP** and a gray scuff pad, paying close attention to textured or recessed areas. Rinse with water. If contamination still exists, water will bead on the surface. Repeat this step until beading no longer occurs.
2. Clean thoroughly with **3834( ) VINYL PREP** using a clean lint free towel and wiping in one direction; or apply **38464 WORLD CLASS™ VINYL/PLATIC PREP** using a clean gray scuff pad. Rinse with water and dry.

#### **Leather:**

1. Clean first with **39362 SEM SOAP** and a gray scuff pad, paying close attention to textured or recessed areas. Wipe with a clean damp towel to remove all residue and allow surface to dry.
2. Clean with **3835( ) PLASTIC/LEATHER PREP**.
3. Scuff the leather with a clean, gray scuff pad or 400-600 grit sandpaper.
4. Clean again with **3835( )**.

**MIXING:**



Agitate thoroughly! Shake can vigorously for one minute after mixing ball rattles to ensure color uniformity and to prevent clogging. **For best results, use only when can temperature is approximately 70°F (21°C).**

**APPLICATION:**



Apply light “mist” coats, allowing 5-10 minutes between coats.

It should be noted that even though film is dry to touch, the substrate should not be subjected to heavy abuse or abrasion for 24 hours.

**NOTE:** Spray tip may be adjusted for either a vertical or horizontal fan spray pattern.

**NOTE:** If clogging develops, remove spray button with a twisting motion and clean with material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

**NOTE:** After each use, turn can upside down and spray several seconds to clear spray tip.

**STORAGE:**



**CLASSIC COAT** should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **CLASSIC COAT** is 3 years when stored under normal conditions.

**TECHNICAL CONSULTATION SERVICE**

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

**DISCLAIMER:** The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.

**SEM Products, Inc.**  
**1685 Overview Dr. Rock Hill SC 29730**  
**Tel: 800/ 831-1122**  
**[www.semproducts.com](http://www.semproducts.com)**