

Specialty Paint & Protective Coatings

# PRODUCT DATA SHEET

# PTI-1022X66 PTI-1022X66 SOLVENT BLEND

# **DESCRIPTION**

PTI-1022x66 is a specially formulated solvent blend that is not photochemically reactive per Rule 66. This product is used as a reducer for Products Techniques, Inc. alkyd topcoats, primers, and some varnish systems.

#### **SOLVENT PROPERTIES & CHARACTERISTICS**

Flash Point	45°F
Weight (lbs per gallon)	6.65 lbs
Color	Clear
Volatile Organic Compounds (VOC)	797 g/l
Specifications	Proprietary

# SHELF LIFE

Shelf life is only applicable for materials stored in unopened and undamaged original factory filled containers. 1 year when stored between 50°-85° Fahrenheit.

# HEALTH, SAFETY, & STORAGE REQUIREMENTS

Refer to each individual material SDS (Safety Data Sheet) for specific requirements on the health, safety, storage and handling requirements. Follow all local, state, and national regulations during surface preparation, material application and cleanup.

# **PRODUCT INFORMATION & DISCLAIMER**

Product Data Sheets are periodically updated to reflect new information. It is important to use the latest and most recent revision for the product being used. The foregoing information is accurate to the best of our knowledge. However, due to differences in customer handling, use and method of application which are not known and are beyond our control, Products Techniques, Inc. makes no warranties as to the end result.

PTI-1022x66\_PDS\_Rev. 01 11/5/2012