DSCH POWER TOOL

BENCH GRINDER DISC - VERY FINE



Quickly remove carbon from pistons and valve stems. Great for light deburring head bolts and studs. One disc is flexible when run alone. Stack as many discs on at a time for the desired finish and removal rate. Safer than a wire wheel, with a much better finish. The very fine grade Bench Grinder Discs are packaged 10 to a

pack, and the medium grade Bench Grinder Discs are packaged 5 to a pack. Size: 8" x 1/2" • Grain: A/O • Grade: Very Fine • Max RPM: 3,000 P/N 12-00849......\$69.75



7"CUTTING WHEEL

1/2" X BRE 1/16" Oxide abrasive wheel - fine abrasive for burr-free cutting of thin wall tubing and applications which require a fine finish.

•Wheel Size: 7" x 1/16" x 1/2" • Max RPM: 8,700 • Weight: 6lbs • Standard Grades: A60TBE 3C14 P/N 09-02564\$5.60

BOSCH TOP HANDLE JIGSAW



Toolless Blade-Change System - Fast insertion, blade ejection lever eliminates need to touch hot blade. Most secure jigsaw clamping system. Features

· Powerful 7.0-Amp Jigsaw - Top jigsaw amp rating. · Variable speed Powerful 7.0-Amp Jigsaw – Top jigsaw amp rating. • Variable speed
Dial sets maximum speed and accelerator trigger controls operating speed. • Constant Response™ circuitry – Maintains desired speed for consistent performance and precision. • Aluminum gearbox with insulated cover • Toolless Blade-Change System – Fast insertion, blade ejection lever eliminates need to touch hot blade. Most secure jigsaw clamping system. • Internal Precision Control - Precision-machined plunging system and low-vibration design for enhanced accuracy and extremely smooth operation. • Large sturdy die-cast foot with steel insert extremely smooth operation. • Large, sturdy die-cast foot with steel insert and on-board bevel wrench. • Exclusive multi-directional blade clamp provides superior grip of T-shank blades. (JS470E does not accept U-Shank blades) · Four orbital-action settings -Different blade strokes for smooth to aggressive cuts. • Adjustable dust blower keeps cutting line

BOSCH 3-1/4 INCH PLANER 120V



Powerful 6.0 amp motor, 16,500 RPM for fast stock removal and a smooth finish. Electronically-counterbalanced, single-blade system automatically positions blade at ideal cutting angle. Reduces drag and provides fast operation and a smooth finish. Eliminates uneven planing caused by misaligned blades. Equipped with Bosch Woodrazor™ micrograin carbide blades. Ratcheting depth knob that allows for fool-proof setting of depth increments from 0" to 1/16" (1.5 mm). Also features an edge guide fence. A protective shield covers the section of blade not in use. Amperage: 6.0. Cord Length: 10'. Country of Origin: Malaysia. No Load RPM: 16,500. Planing Depth: 0 - 1/16" (1.5 mm). Planing Width: 0" to 3-1/4". Rabbet Depth: 5/16". Rating: 120V AC. Shoe Length: 11 - 1/8". P/N 12-02823\$157.75

BOSCH TOP HANDLE JIG SAW **5 INCH RANDOM ORBIT SANDER**



MODEL NO. ROS20VSK

Features:

 Best all-around sanding performance and convenience.
Twistoff translucent dust canister shows dust level and detaches easily. Ant-spillback design prevents dust from spilling on removal. • Bosch Ant-spillback design prevents dust from spilling on removal. • Bosch Microfilter system traps dust particles as small as 1/2 micron. • Hook-Tight[™] hook-and-loop disk attachment ensures firm grip of standard hook-and-loop sanding discs. • Comfortable, ergonomic soft-grip top and body • Integral pad dampening system prevents swirl marks • Soft microcellular backing pad ensures smooth, fine finish on flat or contoured surfaces. • Variable-speed dial allows matching of speed to work piece and took work piece and task P/N 12-01766 \$125.75

AIRCRAFT STATIC TEST ADAPTER



SA3Y-P-UNI-2 Aircraft Static Test Adapter. • Automatically attaches to aircraft fuselage • High pressure hoses with quick release fittings • Press to release button for static adapter removal · Safety check valves for power failure and system leaks · High impact yellow case with internal electric vacuum pump · Designed to fit most general & military aircraft static ports • Comes with 1/2 in center suction cup. Accessory kits are available for specific static ports • Power input: 115 V AC 50/60 Hz. Continuous operation Custom voltages available: 12vdc, 28vdc, 115 vac & 220 vac • Size: 12" x 10" Wt. 8.5lbs.

P/N 13-20266 \$1,560.00

BOSCH 4-1/2 INCH ANGLE GRINDER



Features:

6 Amps, 11,000 RPM · Lock-on/off switch — for extended use applications · Service MinderTM brushes — Eliminates guesswork, stops the tool when preventative maintenance is required • Epoxy Coated Field Windings — Provides ultimate protection against abrasive dust and metal debris • 5/8" -11 Spindle — wide flexibility for mounting most popular accessories • Spindle Lock — For quick wheel changes • Double insulated, UL listed, complies to OSHA • 2-Position auxiliary handle — specifically designed and angled to a "natural" position for maximum comfort and